MIMSAL MEDICAL LIGHTING

	LUXIFLEX LED LUXIFLEX LED PLUS		LUXIFLEX SENSOR LED LUXIFLEX SENSOR LED PLUS		NEW LUXIFLEX LED II LUXIFLEX LED PLUS II		NEW LUXIFLEX SENSOR II LUXIFLEX SENSOR PLUS II		MS FLEX LED MS FLEX PLUS LED		MS LED MS LED PLUS		MS CEILING LED MS CEILING PLUS LED	
Źródło światła	LED 6W 15°	LED 10W 14°	LED 6W 15°	LED 10W 14°	LED 8W	LED 12W	LED 8W	LED 12W	LED 8W	LED 12W	LED 8W	LED 12W	LED 8W	LED 12W
Długość ramienia	85 cm		85 cm		93,5 cm		93,5 cm		70 cm		90 cm		1005 mm ramię, 1000 mm długość mocowania od sufitu	
Budowa ramienia	gęsia szyja		gęsia szyja		gęsia szyja		gęsia szyja		gęsia szyja		przegubowe		przegubowe	
Żywotność lampy	50 000 godzin		50 000 godzin		50 000 godzin		50 000 godzin		50 000 godzin		50 000 godzin		50 000 godzin	
Oddanie barw	> 97%		> 97%		> 80%	> 97%	> 80%	> 97%	> 97%		> 97%		> 97%	
Temperatura barwowa	4 500 °K		4 500 °K		4 000 °K	4 500 °K	4 000 °K	4 500 °K	4 500 °K		4 500 °K		4 500 °K	
Regulowana intensywność światła	✗	✗	✓	✓	✗	✗	✓	✓	✗	✓	✗	✓	✗	✓
Bezdotykowy system włączania / wyłączania	✗	✗	✓	✓	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗
Lux przy 50 centymetrach	15 000	35 000	15 000	35 000	25 000	50 000	25 000	50 000	45 000	65 000	45 000	65 000	45 000	65 000
Gwarancja	5 LAT		5 LAT		5 LAT		5 LAT		5 LAT		5 LAT		5 LAT	
Rodzaje mocowania	Blat Ściana Statyw jezdny		Blat Ściana Statyw jezdny		Blat Ściana Statyw jezdny		Blat Ściana Statyw jezdny		Blat Ściana Statyw jezdny		Blat Ściana Statyw jezdny		Sufit	